

## Rice Lake 78772 Summit 4 x 4 LED Floor Scale Legal for Trade 5000 x 1 lb

The Rice Lake Summit 3000 floor scale and indicator package is an economical choice for many industrial weighing tasks, with a durable low-profile deck that fits well into many material handling environments. This Legal for Trade scale comes with our easy-to-use and straightforward model 120 digital weight display or optional 120 PLUS digital weight display and 20 feet of load cell cable.







## Capacity x Readability

Non Legal Mode:5000 lb

x 1 lb

Legal For Trade: 5000 lb

x 1
Pan Size
4 x 4 ft

Manufature: Rice Lake

SKU: **78772** 



Please Call (800)832-0055

## **Features**

The Rice Lake Summit 3000 floor scale and indicator package is an economical choice for many industrial weighing tasks, with a durable low-profile deck that fits well into many material handling environments. This Legal for Trade scale comes with our easy-to-use and straightforward model 120 digital weight display or optional 120 PLUS digital weight display and 20 feet of load cell cable. Standard Features

- Summit® 3000 Floor Scale
- 4 NTEP Certified alloy steel-shear beam load cells
- Top access junction box
- Rugged diamond safety treadplate steel deck
- 4 adjustable rigid polyurethane rubber feet, 3 in (76.2 mm) diameter
- Signal trim summing board housed in ABS enclosure
- Threaded eyebolt hole (1/2–20NF) located in the center of the deck for easy lifting
- 20 ft of EL147 load cell cable with quick disconnect
- Package configured and calibrated for 5,000 divisions 120 Digital Weight Indicator
- 120 Digital Weight Indicator: Large 0.8 in (20.3 mm) light emitting diode (LED) display
- 120 Digital Weight Indicator:5-button operation
- 120 Digital Weight Indicator: Full front panel digital calibration and configuration 120 PLUS Digital Weight Indicator
- 120 PLUS Digital Weight Indicator:Large 0.8 in backlit liquid crystal display (LCD)
- 120 PLUS Digital Weight Indicator:115 or 230 VAC wall adapter with rechargeable battery

## **Specifications**

| MODEL   | 78772  | 78773              | 106913 106914                            | 78780   | 78781              | 106915 1              | 06916  | 78776  | 78777                | 106917   | 106918               |
|---|--|--------------------|--|---|--------------------|-----------------------|--------|--|----------------------|--|----------------------|
| Capacity x<br>Readabilit  |  | 10000<br>lb x 2 lb | 5000 10000<br>lb x 1 lb lb x 2<br>lb     | 5000<br>lb x 1 lb                                       | 10000<br>lb x 2 lb | 5000                  | x 2    | 2,500<br>kg x<br>0.5 kg  | 5000<br>kg x 1<br>kg | 2,500<br>kg x<br>0.5 kg  | 5000<br>kg x 1<br>kg |
| Legal for<br>Trade  | Base: NTEP CC 92-001A9, Class III 5,000 d<br>Indicator: NTEP CC 03-059, Class III/IIIL 6,000 d |                    |  |   |                    |                       |        | Base: Measurement Canada<br>AM-5530, Class III 5,000 d<br>Indicator: Measurement Canada<br>AM 5517 |                      |  |                      |
| Platform dimensions   | 4 x 4 ft   | 4 x 4 ft           | 4 x 4 ft 4 x 4 ft                        | 4 x 4 ft  | 4 x 4 ft           | 4 x 4 ft 4            | x 4 ft | 4 x 4 ft   | 4 x 4 ft             | 4 x 4 ft   | 4 x 4 ft             |
| Indicator   | 120  |                    | 120 Plus                                 | 120   |                    | 120 Plus              |        | Weights and Measures (120)   |                      | 120 Plus<br>115 VAC<br>Canadian<br>Weights and<br>Measures (120<br>PLUS) |                      |
| Power<br>(Indicator)  | 115 VAC (120)  |                    | 115 VAC (120<br>PLUS)                    | 230 VAC   | C (120)            | 230 VAC (120<br>PLUS) |        |  |                      |  |                      |
| Display   | LED - display 0.8in<br>(20.3mm)6-digit,<br>7-segment   |                    | LCD - display<br>Large 0.8 in<br>backlit | LED - display<br>0.8in<br>(20.3mm)6-digit,<br>7-segment |                    | Large 0.8 in          |        | LED - display<br>0.8in<br>(20.3mm)6-digit,<br>7-segment  |                      | LCD - d<br>Large 0<br>backlit  |                      |
| Cable<br>Length   | 20 ft (6.1 m) (for connecting junction box to indicator)                                       |                    |  |   |                    |                       |        |  |                      |  |                      |
| Warranty  | Summit 3000 weldment and load cells two years, all other components one year                   |                    |  |   |                    |                       |        |  |                      |  |                      |
| Approvals   | NTEP CC 92-001A9, Class III 5,000 d<br>Measurement Canada AM-5530, Class III 5,000 d           |                    |  |   |                    |                       |        |  |                      |  |                      |
| Serial<br>Output  | 7 or 8 data bits; even, odd or no parity   |                    |  |   |                    |                       |        |  |                      |  |                      |
| Printer Port Output-only RS-232 or active 20 mA current loop  EDP Ports Full duplex RS-232 (1200-38400 bps) |  |                    |  |   |                    |                       |        |  |                      |  |                      |

i81u812

Contact US 718-336-5900 Store Policies About Us Returns

Phone: (800)832-0055 or (718)336-5900
Chat with us via WhatsApp Chat
Address: 4802 Glenwood Rd. Brooklyn, NY 11234
© 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.