

No matter what you're weighing, the new Entris® II is always the right choice. Offering unrivalled value at a budget price, this is the only balance in its class featuring isoCAL, LED touch technology and 12 builtin applications. Backed by almost 150 years of German engineering expertise, and available in 40 different models, you'll easily find an Entris® II balance that exactly meets your specific weighing needs. Entris II BCE223-1S Milligram Balance with Internal Calibration 220 g x 1 mg


Capacity x Readability

220 g x 1 mg

Pan Size

120 mm (Diameter)

Manufacture: Sartorius

SKU: BCE223i-1S

Weight: 8.00 lb

Free Ground Shipping within the 48 continental US States

Please Call
(800)832-0055

Features

Entris® II Laboratory Balances

Entris® II — Best Value in its Class for Basic Weighing Tasks. Every Sartorius balance offers quality, value and consistency

No matter what you're weighing, the new Entris® II is always the right choice. Offering unrivalled value at a budget price, this is the only balance in its class featuring isoCAL, LED touch technology and 12 builtin applications. Backed by almost 150 years of German engineering expertise, and available in 40 different models, you'll easily find an Entris® II balance that exactly meets your specific weighing needs.

Quality, Value and Consistency For accurate weighing results you can trust time after time

- **Highest quality standards engineered in Germany**
- Highly accurate results year in and year out -- guaranteed via monolithic weigh cell technology invented by Sartorius*
- Fastest stabilization time in its class -- using state-of-the-art weighing sensors
- Best repeatability -- with rectangular weighing pan
- Overload protection -- rugged design weighs up to a pre-set amount
- Guaranteed reliability -- with the self-test "@start"
- Made in Germany
- **Easy clean for operational efficiency and durability**
- High chemical resistance -- ensured using parts made from hard-wearing polybutylene terephthalate (PBT), stainless steel and glass
- Prevents cross contamination -- with wipe clean design and easy-to-remove parts

Effective draft shield

- Minimizes weighing errors caused by electrostatically charged samples -- using specially coated glass parts

Innovations in this Weighing Class For efficient, user-friendly operation

- **isoCAL (internal calibration and adjustment) for total assurance of accurate weighing results**
- Optimal accuracy and operating convenience -- using fully automated internal temperature and time-controlled calibration and adjustment feature, unique in this weighing class
- Assures (SOP) compliant operation -- with self-notification if calibration is outside the normal range
- **Hybrid screen for excellent readability and use**
- Combines intuitive, wear resistant LED and touch technology -- provides an easy and clear structured user interface
- **Plug-and-play convenience**
- Automatically detects Sartorius accessories (e.g. printer, second display)
- Real "PC-direct feature" for easy connection to a PC to transfer weighing data directly into spreadsheets or documents such as Microsoft® Excel or Word
- **Data output for dynamic weighing applications**
- Configurable time interval for data output
- **Easily adapts to your ambient conditions**
- With just one click on the home screen

| Specifications | |
|----------------|-------------------------|
| Model | Model 1000 |
| Material | Material A |
| Dimensions | Dimensions 100x100x100 |
| Weight | Weight 100g |
| Color | Color Blue |
| Finish | Finish Matte |
| Usage | Usage Industrial |
| Warranty | Warranty 1 Year |
| Price | Price \$100 |
| Availability | Availability In Stock |
| Lead Time | Lead Time 1 Week |
| Shipping | Shipping Free |
| Support | Support 24/7 |
| Documentation | Documentation Available |
| Compliance | Compliance CE |
| RoHS | RoHS Compliant |
| REACH | REACH Compliant |
| ISO 9001 | ISO 9001 Certified |
| ISO 14001 | ISO 14001 Certified |
| ISO 45001 | ISO 45001 Certified |
| ISO 50001 | ISO 50001 Certified |
| ISO 26262 | ISO 26262 Certified |
| ISO 27001 | ISO 27001 Certified |
| ISO 28000 | ISO 28000 Certified |
| ISO 31000 | ISO 31000 Certified |
| ISO 34000 | ISO 34000 Certified |
| ISO 37000 | ISO 37000 Certified |
| ISO 38000 | ISO 38000 Certified |
| ISO 39000 | ISO 39000 Certified |
| ISO 40000 | ISO 40000 Certified |
| ISO 41000 | ISO 41000 Certified |
| ISO 42000 | ISO 42000 Certified |
| ISO 43000 | ISO 43000 Certified |
| ISO 44000 | ISO 44000 Certified |
| ISO 45000 | ISO 45000 Certified |
| ISO 46000 | ISO 46000 Certified |
| ISO 47000 | ISO 47000 Certified |
| ISO 48000 | ISO 48000 Certified |
| ISO 49000 | ISO 49000 Certified |
| ISO 50000 | ISO 50000 Certified |
| ISO 51000 | ISO 51000 Certified |
| ISO 52000 | ISO 52000 Certified |
| ISO 53000 | ISO 53000 Certified |
| ISO 54000 | ISO 54000 Certified |
| ISO 55000 | ISO 55000 Certified |
| ISO 56000 | ISO 56000 Certified |
| ISO 57000 | ISO 57000 Certified |
| ISO 58000 | ISO 58000 Certified |
| ISO 59000 | ISO 59000 Certified |
| ISO 60000 | ISO 60000 Certified |
| ISO 61000 | ISO 61000 Certified |
| ISO 62000 | ISO 62000 Certified |
| ISO 63000 | ISO 63000 Certified |
| ISO 64000 | ISO 64000 Certified |
| ISO 65000 | ISO 65000 Certified |
| ISO 66000 | ISO 66000 Certified |
| ISO 67000 | ISO 67000 Certified |
| ISO 68000 | ISO 68000 Certified |
| ISO 69000 | ISO 69000 Certified |
| ISO 70000 | ISO 70000 Certified |
| ISO 71000 | ISO 71000 Certified |
| ISO 72000 | ISO 72000 Certified |
| ISO 73000 | ISO 73000 Certified |
| ISO 74000 | ISO 74000 Certified |
| ISO 75000 | ISO 75000 Certified |
| ISO 76000 | ISO 76000 Certified |
| ISO 77000 | ISO 77000 Certified |
| ISO 78000 | ISO 78000 Certified |
| ISO 79000 | ISO 79000 Certified |
| ISO 80000 | ISO 80000 Certified |
| ISO 81000 | ISO 81000 Certified |
| ISO 82000 | ISO 82000 Certified |
| ISO 83000 | ISO 83000 Certified |
| ISO 84000 | ISO 84000 Certified |
| ISO 85000 | ISO 85000 Certified |
| ISO 86000 | ISO 86000 Certified |
| ISO 87000 | ISO 87000 Certified |
| ISO 88000 | ISO 88000 Certified |
| ISO 89000 | ISO 89000 Certified |
| ISO 90000 | ISO 90000 Certified |
| ISO 91000 | ISO 91000 Certified |
| ISO 92000 | ISO 92000 Certified |
| ISO 93000 | ISO 93000 Certified |
| ISO 94000 | ISO 94000 Certified |
| ISO 95000 | ISO 95000 Certified |
| ISO 96000 | ISO 96000 Certified |
| ISO 97000 | ISO 97000 Certified |
| ISO 98000 | ISO 98000 Certified |
| ISO 99000 | ISO 99000 Certified |
| ISO 100000 | ISO 100000 Certified |

| | | | | | | | | | | |
|--|--|--|-----------------|-----------------|------------------------|-----------------|-----------------|-----------------|--------------------|-------------|
| Models with External Calibration | | BCE64-1S | BCE124-1S | BCE224-1S | BCE223-1S | BCE323-1S | BCE423-1S | BCE623-1S | BCE653-1S | |
| Models with Internal Calibration | | BCE64i-1S | BCE124i-1S | BCE224i-1S | BCE223i-1S | BCE323i-1S | BCE423i-1S | BCE623i-1S | BCE653i-1S | |
| Legal for Trade | | BCE124-1NUS | | | BCE224-1NUS | - | - | - | BCE623-1NUS | BCE653-1NUS |
| Capacity x Readability | | 60 g x 0.1 mg | 120 g x 0.1 mg | 220 g x 0.1 mg | 220 g x 1 mg | 320 g x 1 mg | 420 g x 1 mg | 620 g x 1 mg | 650 g x 1 mg | |
| Repeatability | At 5% load, typical value | 0.08 mg | 0.08 mg | 0.08 mg | 0.5 mg | 0.5 mg | 0.5 mg | 0.5 mg | 0.5 mg | |
| | At approx. maximum load, typical value | 0.1 mg | 0.1 mg | 0.1 mg | 1 mg | 1 mg | 1 mg | 1 mg | 1 mg | |
| Linearity deviation | Limits | 0.2 mg | 0.2 mg | 0.2 mg | 2 mg | 2 mg | 2 mg | 2 mg | 2 mg | |
| | Typical value | 0.06 mg | 0.06 mg | 0.06 mg | 0.6 mg | 0.6 mg | 0.6 mg | 0.6 mg | 0.6 mg | |
| Sensitivity drift between +10 °C and +30 °C | | 1.5 ± ppm/K | 1.5 ± ppm/K | 1.5 ± ppm/K | 2 ± ppm/K | 2 ± ppm/K | 2 ± ppm/K | 2 ± ppm/K | 2 ± ppm/K | |
| isoCAL (only for i-1x models) | Temperature change | 1.5 K | 1.5 K | 1.5 K | 2 K | 2 K | 2 K | 2 K | 2 K | |
| | Time interval | 4 h | 4 h | 4 h | 6 h | 6 h | 6 h | 6 h | 6 h | |
| Tare maximum capacity (subtractive) | | | | | | | | | | |
| Minimum initial weighing according to USP (United States Pharmacopeia), Chap. 41 | Optimum minimum initial weighing | 0.082 g | 0.082 g | 0.082 g | 0.82 g | 0.82 g | 0.82 g | 0.82 g | 0.82 g | |
| | Optimum minimum initial weighing | 0.16 g | 0.16 g | 0.16 g | 1 g | 1 g | 1 g | 1 g | 1 g | |
| Typical measurement time | | ≤ 2.0 s | ≤ 2.0 s | ≤ 2.0 s | ≤ 1.5 s | ≤ 1.5 s | ≤ 1.5 s | ≤ 1.5 s | ≤ 1.5 s | |
| Weighing pan size | | 90 mm dia (3.54 inch) | | | 120 mm dia (4.72 inch) | | | | | |
| Weighing chamber height | | 240 mm | | | | | | | 50 mm | |
| Net weight, approx. | | 5.9 kg | | | | | | | 4.5 kg | |
| Shipping weight, approx. | | 7.70 kg | | | | | | | 5.80 kg | |
| Recommended calibration weight | External calibrated test weight | 50 g | 100 g | 200 g | 200 g | 200 g | 200 g | 500 g | 500 g | |
| | Optimum minimum initial weighing | <div>View</div> | <div>View</div> | <div>View</div> | <div>View</div> | <div>View</div> | <div>View</div> | <div>View</div> | <div>View</div> | |
| | | E2 ** | E2 ** | E2 ** | F1 ** | F1 ** | F1 ** | F1 ** | F1 ** | |
| Dimensions, D x W x H | | 317 x 219 x 345 mm | | | | | | | 317 x 219 x 146 mm | |
| Installation site | | For indoor use only, max. height above sea level: 3000 m | | | | | | | | |
| Temperature | | Environment (metrological data): +10 - +30 °C Environment: +5 - +40 °C Storage and transport: -10 - +60 °C | | | | | | | | |
| Relative humidity | | At temperatures up to 31° C, non-condensing, then linear decrease from max. 80 % at 31° C to max. 50 % at 40° C: 15 - 80 % | | | | | | | | |
| Power Supply Device | | Input voltage 15 VDC (±10 %) - Power consumption, max: 4 W Only by Sartorius power supply unit YEPS01-15V0W with interchangeable country-specific plug-in AC adaptors | | | | | | | | |
| Weighing pan | | Stainless steel | | | | | | | | |
| Device Warm-up Time approx | | 2 h | | | | | | | | |
| Interface RS232 | | Interface operation: Full duplex Connection: D-sub connector, 9-pin Pin 1: Not assigned - Pin 2: Data output (TxD) - Pin 3: Data input (RxD) - Pin 4: Not assigned - Pin 5: Internal ground - Pin 6: Not assigned - Pin 7: Clear to Send (CTS) - Pin 8: Request to Send (RTS) - Pin 9: Universal key | | | | | | | | |
| Interface USB-C | | USB UTL Connectable devices: Sartorius printers, Sartorius second display or PC | | | | | | | | |
| Calibration | | Internal calibration isoCAL (models with marking i-1x) or External calibration | | | | | | | | |
| Selectable Weight Units | | Gram, kilogram, carat, pound, ounce, troy ounce, Hong Kong tael, Singapore tael, Taiwan tael, grain, pennyweights, milligram, parts per pound, China tael, mommes, Austrian carat, tola, baht, mesghal and Newton | | | | | | | | |
| Display | | Intuitive, wear resistant LED screen with touch technology | | | | | | | | |

Built-in Applications

• Weighing | Dosing • Counting • Percentage weighing • Mixing | Net total • Components | Totalizing • Animal weighing • Calculation | Free factor • Density determination • Underfloor weighing feature for bigger samples • Statistics • Peakhold • Checkweighing • Mass unit conversion

Languages

English, German, France, Italian, Spanish, Portuguese, Russian, Polish

Protection

• Chemical resistant housing parts • Glass parts of the draft shield are coated to reduce electrostatic influences • Display foil (available as assessorY) • Dust cover for balances with draft shield

i81u812

- Contact US
- 718-336-5900
- Returns
- Store Policies
- About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
 - Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.