Setra Super II 4091361NB Counting Scale with Battery Option 35 x 0.0005 lb



A superior counting scale, the Super II combines incredible accuracy with easy-to-read text prompts enhanced by a backlit display. It's internal database, bar code label making, set points and multiple base connectivity make it truly flexible. Input to the database can be entered on most computer keyboards or from the user friendly, cell phone style keypad.



Features

The Setra Super II combines incredible accuracy with easy-to-read, text prompts. With an internal database, bar code label making, set points and multiple base connectivity, the Super II is truly flexible. Input to the database can be entered with most computer keyboards or from the user friendly, cell phone style keypad. The scale menu that orders up a wide selection of features is easy to access, easy to navigate and easy to exit. Use it to build a log of daily transactions, customize display prompts, or set the optimal sample size for counting. Multiple ports keep you constantly connected...to a scanner, to a printer, to a computer, to your bulk weighing scale and to up to eight bases. Super II is unquestionably the superior choice in count-ing scales for all your receiving, kitting and inventory needs.

A superior counting scale, the Super II combines incredible accuracy with easy-to-read text prompts enhanced by a backlit display. Its internal database, bar code label making, set points and multiple base connectivity make it truly flexible. Input to the database can be entered on most computer keyboards or from the user friendly, cell phone style keypad.

The scale menu that orders up a wide selection of features is easy to access, easy to navigate and easy to exit. Use it to build a log of daily transactions, customize display prompts, or set the optimal sample size for counting. Multiple ports keep you constantly connected...to a scanner, to a printer, to a computer, to your bulk weighing scale and up to eight bases. Super II is unquestionably the superior choice in counting scales for all your inventory, kitting, and checkweigh needs.

- Backlit Display (optional)
- Paperless inventory with onboard database
- Checkweighing using set-points
- Sturdy, all metal construction for long life
- Graphic LCD to provide easily customized messages
- Macros offering simplified one-key operation
- Comm ports for simultaneous connection to a printer, a scanner, and a PC
- Speedy transaction processing and data logging

- Effortless keyboard data entry optional QWERTY keyboard
 Portable operation optional internal battery
 Multiple bases operated by one controller remote scale option
 English & bar coded labels optional Dymo Setra 300 printer

Specifications

	Setra	Super II Cour	nting Scales	with Battery	Option				
Battery Option Models	4091321NB	4091331NB	4091351NB	4091361NB	4091371NB	4091381NB	4091391NB		
Battery Option with Remote Scale Option	4091321RB	4091331RB	4091351RB	4091361RB	4091371RB	4091381RB	4091391RB		
Battery Option Models w Backlight	4091421NB	4091431NB	4091451NB	4091461NB	4091471NB	4091481NB	4091491NB		
Battery Option with Remote Scale Option and Backlight	4091421RB					4091481RB			
Capacity x	4.4 x 0.00005 lb	11 x 0.0002 Ib	27 x 0.0005 lb	35 x 0.0005 lb	55 x 0.001 Ib	65 x 0.001 Ib	110 x 0.002 lb		
Readability	2 x 0.00002 Kg	5 x 0.00005 Kg	12 x 0.0002 Kg	16 x 0.0002 Kg	25 x 0.0005 Kg	30 x 0.0005 Kg	50 x 0.001 Kg		
MAXIMUM READABILITY	0.000002 Kg 0.000005 lb	0.000005 Kg 0.00002 lb	0.00002 Kg 0.00005 lb	0.00002 Kg 0.00005 lb	0.00005 Kg 0.0001 lb	0.00005 Kg 0.0001 lb	0.0001 Kg 0.0002 lb		
LINEARITY ERROR	± 0.00002 Kg ± 0.0005 lb	± 0.00005 Kg ± 0.002 lb	•	± 0.0002 Kg ± 0.0005 lb	•	± 0.0005 Kg ± 0.001 lb	± 0.001 Kg ± 0.002 lb		
Internal Resolution	Selectable up to 1 Part in 1,000,000								
Displayed Resolution:	Selectable								
Units of Measure	nits of Measure Pounds, kilograms, grams, ounces, pennyweights, troy ounces, carats, grains (user-definable unit)								
Display Update Rate	Selectable, 5 settings								
Counting Capacity	10,000,000 pieces								
Memory	750 records including part number (23 characters), description(16 characters), lot number (16 characters), count, average piece weight, tare, set points								
Time and Date	Time and Date Battery protected real time clock								
Data Communications	Bi-directional RS-232 port for PC; OUT port for printer; IN port for scanner, KEYBOARD port for QWERTY PS/2 (6 pin mini DIN)						RD port for		
Selectable Baud Rates	1200, 2400, 4800, 9600 (Com 1, 2, and 3)								
Pan	Stainless Steel								
Operating Temperatures	40° to 110°F (5° to 43°C) 10 to 90% RH non-condensing								
Power		Inter	nal or Extarna	al Rechargea	ble Battery				
Pan Size W x D	6.2" diam	ter 11.5" x 9.5"			13" x 15.25"				
Dimensions W x D x H	11.5" x 9.5" x 4.75"		11.5" x 9.5" x 4.75"		13	13" x 15.25" x 4.5"			
Shipping Weight	40 lb		20	lb		16 lb			

Certifications Limited Warranty			UL, CSA, CE, ISO 9001 Two years								
	i81u812										
	C	Contact US	718-336-5900	Returns	Store Policies	About Us					
		Phone: <u>(800)832-0055</u> or <u>(718)336-5900</u> Chat with us via <u>WhatsApp Chat</u> Address: 4802 Glenwood Rd. Brooklyn, NY 11234 © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.									