

The NTEP Approved AHS hanging scale from Intelligent Weighing Technology. UWE AHS-15 (3-AHS-S150-022) Intelligent-Weigh NTEP Hanging Scale 15 x 0.01 lb is easy to use and portable



**Capacity x  
Readability**

Non Legal  
Mode: 15 lb x 0.01  
lb  
Legal For Trade:  
15 lb x 0.01 lb

**Manufacture:** UWE

**SKU:** AHS-15

**UPC:**

738964615038

**Weight:** 2.00 lb

Free Ground Shipping  
within the 48  
continental US States



Legal for Trade

**Please Call  
(800)832-0055**

## Features

The NTEP Approved AHS hanging scale from Intelligent Weighing Technology. Features & Benefits

- NTEP Approved Legal For Trade
- Simple
- Digital Functionality
- Battery Operated
- Lightweight
- Easy to Use
- Hold Function
- Optional Hanging Pan Available
- Made in Democratic Taiwan

## Specifications

| Model                               | AHS-6   | AHS-15                     | AHS-30                            | AHS-60                          |
|-------------------------------------|---|----------------------------|-----------------------------------|---------------------------------|
| <b>Capacity x Readability</b>       | 6 x 0.005 lb<br>2.7 kg x 2 g  | 15 x 0.01 lb<br>5 kg x 5 g | 30 x 0.02 lb<br>13.6 kg x 0.01 kg | 60 x 0.05 lb<br>27 kg x 0.02 kg |
| <b>Platform Size (W x D x H)</b>    | Optional 12 inch diameter stainless steel hanging pan and cantilever beam                   |                            |                                   |                                 |
| <b>Legal for Trade</b>              | NTEP #18-098  |                            |                                   |                                 |
| <b>Weighing Units / Functions</b>   | g (kg), lb  |                            |                                   |                                 |
| <b>Stabilization Time (seconds)</b> | < 2   |                            |                                   |                                 |
| <b>Tare Range</b>                   | To capacity by subtraction  |                            |                                   |                                 |
| <b>Safe overload</b>                | 200% of rated capacity – ultimate overload 300%   |                            |                                   |                                 |
| <b>Power Source</b>                 | 4 size “C” type batteries (not included) or external power adapter (not included)           |                            |                                   |                                 |
| <b>Construction</b>                 | ABS Plastic   |                            |                                   |                                 |
| <b>Display</b>                      | 1 in / 25.4 mm, 7 segment, wide viewing angle backlit LCD                                   |                            |                                   |                                 |
| <b>Operating Environment</b>        | 14 F to 104 °F non-condensing R.H. ≤ 85%  |                            |                                   |                                 |
| <b>Dimensions (W x D x H)</b>       | 4.72 x 2.25 x 7.25 in / 120 x 57 x 185 mm   |                            |                                   |                                 |
| <b>Net Weight</b>                   | 1 lb / 1.5 kg   |                            |                                   |                                 |
| <b>Shipping Weight</b>              | 2 lb / 0.9 kg   |                            |                                   |                                 |
| <b>Options</b>                      | 12 inch Diameter Stainless Steel Hanging Pan, AC/DC Power Adapter, Traveler™ Transport Case |                            |                                   |                                 |

| Features                    | Benefits  |
|-----------------------------|---|
| <b>Lightweight</b>          | Easy to use   |
| <b>Large display</b>        | Can be easily read in less than ideal conditions                                    |
| <b>Battery operation</b>    | Allows 250 hours of non-stop operation  |
| <b>Automatic power save</b> | Conserves battery power   |
| <b>Hold function</b>        | Allows the last displayed weight to remain after the load is removed from the scale |
| <b>Auto Zero tracking</b>   | Ensures that you always start weighing at zero                                      |

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.