

The UWE TitanN and the UWE TitanF are Legal for Trade Industrial Bench Scales. These great scale are Cast Aluminum Base with Stainless Platter and come with a Rechargeable Battery. In two sizes 14 x 18 inch and 16.5 x 20.5.



**Capacity x Readability**

Non Legal  
Mode: 200 lb x  
0.05 lb

Legal For Trade:  
200 lb x 0.05 lb

**Pan Size**

14 x 18 in

Manufacture: UWE

SKU:

**15-TIN-1020-112**

Weight: 25.00 lb

Free Ground Shipping  
within the 48  
continental US States



Legal for Trade

**Please Call  
(800)832-0055**

## Features

The UWE TitanN and the UWE TitanF are Legal for Trade Industrial Bench Scales. These great scale are Cast Aluminum Base with Stainless Platter and come with a Rechargeable Battery. In two sizes 14 x 18 inch and 16.5 x 20.5.

- Legal for Trade
- Rechargeable Battery
- Cast Aluminum Base with Stainless Platter
- RS 232 / 485 Interface
- Real Time Clock

## Specifications

Model	TitanN B50	TitanN B100	TitanN B200	TitanF F100	TitanF F200	TitanF F500
<b>Capacity x</b>	50 x 0.01	100 x 0.02	200 x 0.05	100 x 0.02	200 x 0.05	500 x 0.1
<b>Readability</b>	lb	lb	lb	lb	lb	lb
	25 x 0.005	50 x 0.01	100 x 0.02	50 x 0.01	100 x 0.02	250 x 0.05
	kg	kg	kg	kg	kg	kg
<b>Platform Size (W x D x H)</b>	14 x 18 x 3.5" 330 x 450 x 95 mm			16.5 x 20.5 x 4.7" 420 x 520 x 120 mm		
<b>Legal for Trade Divisions</b>	NTEP CoC #12-077A1					
<b>Divisions</b>	5000					
<b>Weighing Units</b>	lb, kg					
<b>Stabilization Time</b>						
<b>Functions</b>	Animal Weighing					
<b>Tare Range</b>	To capacity by subtraction					
<b>Power Source</b>	Built-in rechargeable battery or external power adapter (included)					
<b>Construction</b>	Stainless steel platform with cast aluminum base					
<b>Display</b>	1" High backlit LCD Display					
<b>Operating Environment</b>	32°F to 104°F					
<b>Connectivity</b>	RS 232 / 485 Interface					
<b>Net Weight</b>	25 lb			36 lb		
<b>Shipping Weight</b>	35 lb			46 lb		
<b>Options</b>	Printer, Dry Cell Battery Pack, Wheel Kit					

### Features

### Benefits

<b>Overload and shock protection mechanism</b>	Protects against excessive loads and shock applied to platform
<b>Heavy duty rugged construction</b>	Will withstand harsh industrial operation
<b>Low profile, compact size</b>	Space saving, easy to load and unload
<b>Large backlit LCD display with wide viewing angle</b>	Easy to see weight values from a distance, reduces mistakes
<b>Display reads in lb and kg</b>	Flexibility of operation
<b>Built-in rechargeable battery or external power adapter</b>	Portability. Battery operation minimum 36 hours
<b>Accumulation function</b>	Allows you to add together consecutive weights to arrive at total
<b>Zero tracking</b>	Ensures that you always start weighing at zero
<b>Automatic power save</b>	Conserves battery power
<b>Low battery indicator / charge status indicator</b>	Alerts you to charge the battery, saving downtime

<b>Easy calibration function</b>	Ensures accuracy
<b>Gravitational correction software</b>	Enables you to input different G acceleration factors
<b>Adjustable feet and spirit level</b>	Scale remains level for accurate results on uneven working surfaces - Anti-slip
<b>Digital motion filtering</b>	Enables animal weighing or can compensate for harsh environmental conditions
<b>Operational automatic tare</b>	Enables you to disregard the first item places on the platform

i81u812

[Contact US](#)

[718-336-5900](#)

[Returns](#)

[Store Policies](#)

[About Us](#)

- Phone: [\(800\)832-0055](#) or [\(718\)336-5900](#)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2020 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.