

UWE UFM-F300 (3-UFM-S300-112) Stainless Steel 16.5 x 20.5 inch Legal for Trade Bench Scale 600 x 0.1 lb

The UWE UFM-Series is Legal for Trade Bench Scales and are IP67 Washdown. Made with Stainless Steel and a Built-in rechargeable battery. Use the RS-232 port to connect to printers and computers. Comes in three different base sizes 13 x 17.7 Inches . 16.5 x 20.5 Inches or 19.7 x 23.6 Inches.



Capacity x Readability

Non Legal Mode: 600 lb x
0.1 lb

Legal For Trade: 600 lb x 0.1 lb

Pan Size

16.5 x 20.5 in

Manufacture: UWE
SKU: 3-UFM-S300-112

Weight: 24.00 lb

Free Ground Shipping within
the 48 continental US States



Legal for Trade

**Please Call
(800)832-0055**

Features

The UWE UFM-Series is Legal for Trade Bench Scales and are IP67 Washdown. Made with Stainless Steel and a Built-in rechargeable battery. Use the RS-232 port to connect to printers and computers. Comes in three different base sizes 13 x 17.7 Inches , 16.5 x 20.5 Inches or 19.7 x 23.6 Inches.

- NTEP Approved 6,000 Divisions
 - 60 lb to 1,200 lb Capacity
 - Large 2 Inch Backlit Display
 - Rechargeable Battery
 - 3 Inch Wheel Kit Available
 - Configurable RS232 Interface
-
- Large 2 inch LCD display with wide viewing angle – easy to see weight values from a distance, reduces mistakes
 - Built-in rechargeable battery and external power adapter – portability, battery lasts a minimum of 120 hours (without backlight)
 - Heavy duty rugged construction – will withstand harsh industrial operation
 - Accumulation function – allows you to add together consecutive weights to arrive at a total
 - Gravitational correction software – enables you to input different G acceleration factors
 - Made in Democratic Taiwan

Specifications

Model	UFM-B30	UFM-B60	UFM-B150	UFM-F30	UFM-F60	UFM-F120	UFM-F300	UFM-L60	UFM-L120	UFM-L300	UFM-L600
Capacity x Readability	60 x 0.02 lb	150 x 0.05 lb	300 x 0.1 lb	60 x 0.01 lb	120 x 0.02 lb	250 x 0.05 lb	600 x 0.1 lb	120 x 0.02 lb	250 x 0.05 lb	600 x 0.1 lb	1200 x 0.2 lb
	30 x 0.01 kg	60 x 0.02 kg	150 x 0.05 kg	30 x 0.005 kg	60 x 0.01 kg	120 x 0.02 kg	300 x 0.05 kg	60 x 0.01 kg	120 x 0.02 kg	300 x 0.05 kg	600 x 0.1 kg
	13 x 17.7 x 3.5 inches			16.5 x 20.5 x 4.5 inches				19.7 x 23.6 x 4.5 inches			
Platform Size (W x D x H)	330 x 450 x 90 mm			420 x 520 x 120 mm				500 x 600 x 120 mm			
Legal for Trade	NTEP CoC #04-100										
Divisions	3,000			6,000							
Weighing Units	lb, kg										
Functions	Accumulation										

NEMA / IP Rating	NEMA 4X / IP 67 Protection		
Tare Range	To capacity by subtraction		
Power Source	Built-in rechargeable battery or external power adapter (included)		
Construction	Stainless steel platform and cast aluminum base		
Display	2 inch / 50.8 mm, 7 segment, wide viewing angle backlit LCD		
Overall Dimensions (W x D x H)	13 x 20.7 x 28.3 inches 330 x 525 x 720 mm	16.5 x 23.5 x 33.9 inches 420 x 596 x 860 mm	19.7 x 25.5 x 33.9 inches 500 x 647 x 860 mm
Operating Environment	32°F to 104°F		
Connectivity	RS232 interface configurable, for printer or computer interface		
Net Weight	24.2 lb / 11 kg	24.2 lb / 11 kg	56 lb / 25.4 kg
Shipping Weight	30 lb / 13.6 kg	30 lb / 13.6 kg	63 lb / 28.4 kg
Options	Weatherproof indicator cover, printer, dry cell battery pack, desk mount indicator, wheel kit		

Features	Benefits
Overload and shock protection mechanism	Protects against excessive loads and shock applied to platform
Heavy duty rugged construction	Will withstand harsh industrial operation
Low profile, compact size	Space saving, easy to load and unload
Large backlit LCD display with wide viewing angle	Easy to see weight values from a distance, reduces mistakes
Display reads in lb and kg	Flexibility of operation
Built-in rechargeable battery or external power adapter	Portability. Battery operation minimum 100 hours(without backlight)
Accumulation function	Allows you to add together consecutive weights to arrive at a total
Zero tracking	Ensures that you always start weighing at zero
Automatic power save	Conserves battery power
Low battery indicator / charge status indicator	Alerts you to charge the battery, saving downtime
Easy calibration function	Ensures accuracy
Gravitational correction software	Enables you to input different G acceleration factors
Adjustable feet and spirit level	Scale remains level for accurate results on uneven working surfaces - Anti-slip
Digital motion filtering	Enables animal weighing or can compensate for harsh environmental conditions
Optional automatic tare	Enables you to disregard the first item placed on the platform
In use cover (for indicator)	Protects indicator from damage and dirt

i81u812

Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
- Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234

© 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.