



Cambridge CSW-10AT LED Digital Weight Indicator Legal for Trade

Cambridge CSW-10AT Digital Weight Indicator Legal for Trade, Selectable: NTEP 5,000 Division - Non-NTEP 20,000 Division. Keypad Calibration with Audit Trail. ABS Plastic Dust-Tight Enclosure with Stainless Steel Swivel Stand. Adjustable Motion Detection.



C A M B R I D G E
SCALE WORKS INCORPORATED

Manufacture: Cambridge Scale
SKU: **CSW-10AT**
Dimensions
X: 8.50 Y: 7.00 Z: 3.00
Weight: 7.00 lb

Please Call (800)832-0055

Features

Cambridge CSW-10AT Digital Weight Indicator Legal for Trade

- Selectable: NTEP 5,000 Division - Non-NTEP 20,000 Division
- Net/Gross Display Modes
- Full Range Auto Tare
- Adjustable Digital Filtering
- All Push-button Controls
- LED Display (Bright)
- Printer Data Output on Demand
- 9 Pin Load Cell Connection
- Simple No-Soldering Load Cell Connection
- Clearly, Visible Center of Zero Indication on Display
- Lb/Kg Conversion
- Keypad Calibration with Audit Trail
- Weight Totalization 1 to 5 points of Digital Calibration available
- Span Adjustment at Increasing or Decreasing Weights
- Full Range Push Button Zero
- (1) RS-232 Port for Interface with:
 - Printer Output of Gross/Tare/Net
 - Computer Data Output
 - Scoreboard Continuous Output Alphanumeric or Numeric
- AC Adapter Provided
- Auto Zero Tracking
- Adjustable Motion Detection

- ABS Plastic Dust-Tight Enclosure with Stainless Steel Swivel Stand

Applications:

- Floor Scales
- Bench Scales
- Hopper Scales
- Tank Scales
- Fork Lift Scales
- General Purpose Weighing
- Remote Display Configuration

Optional Features: Models CSW-10AT

- 110 VAC Dry Contact Set Point
- 12 VDC Accessory Port Power Cable
- Peak Weight Hold
- Digital Scroll Tare
- Scale Warning System - strobe light with audible warns operator when sets limits have been exceeded
- WiFi transmitter to customers wireless hub
- Ethernet Connection

Specifications

Model	CSW-10AT	CSW-10AT-B	SSCSW-10AT	SSCSW-10AT-B
Power	120 VAC Adapter / 12 VDC ±10%	7.4 VDC 3000 mAh* Battery/120 VAC Adapter	120 VAC Adapter / 12 VDC ±10%	7.4 VDC 3000 mAh* Battery/120 VAC Adapter
Battery Operated	NO	YES	NO	YES
NON-NTEP Resolution	20,000 Division			
Legal for Trade	NTEP #06-070A1 Measurement Canada #AM-5778C NTEP Resolution 5000 Division			
Humidity	0-90% Non-condensing			
Dimensions	6.5" x 4.3" x 2.5" without Stand, +1 inch with Stand		7.5" x 4.5" x 3" without Stand, +1 inch with Stand	
Enclosure	ABS Plastic		304 Stainless Steel NEMA 4X	
Display	High Efficient, Bright (Adjustable)LED—6 Digits—0.56" High			
Input	0-15mv			
Temperature	10° to +40° Celsius			
Linearity	0.001% of Full Scale			
Accuracy	0.001% of Full Scale			
Load Cell Supply	5VDC at 150ma (8 each 350 ohm load cells)			
Battery Operating Time	-	(1) 350 OHM Cell - 22hrs (4) 350 OHM Cell - 20hrs (8) 350 OHM Cell - 14hrs	-	(1) 350 OHM Cell - 22hrs (4) 350 OHM Cell - 20hrs (8) 350 OHM Cell - 14hrs
Ports	RS-232			
Country of Origin	USA			

i81u812

[Contact US](#)

[718-336-5900](tel:718-336-5900)

[Returns](#)

[Store Policies](#)

[About Us](#)

• Phone: [\(800\)832-0055](tel:800-832-0055) or [\(718\)336-5900](tel:718-336-5900)

• Address: 4802 Glenwood Rd. Brooklyn, NY 11234

• © 2000 - 2019 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.

