



Cambridge SSCSW-20AT LED Indicator Stainless Steel Legal for Trade with Full Numeric Keypad

Cambridge CSW-20AT & CSW-20AT-B & SSCSW-20AT & SSCSW-20AT-B Digital Weight Indicators Legal for Trade, Full Numeric Keypad and two RS-232



C A M B R I D G E
SCALE WORKS INCORPORATED

Manufacture: Cambridge Scale
SKU: SSCSW-20AT
Dimensions
X: 8.50 Y: 7.00 Z: 3.00
Weight: 7.00 lb

Please Call (800)832-0055

Features

Standard Features Include

- Stainless Steel Nema 4X Enclosure
- Stainless Steel Swivel Stand
- 6-Digit .56" Red LED Display
- 6-Pin Watertight Signal Cable Connections
- No Solder Strain Relief Communication Connections
- Red LED Annunciators
- Full Numeric Keypad
- 1 to 5 Points of Linearization
- Span Adjustment at Increasing or Decreasing Weights
- Keypad Configuration & Calibration with Audit Trail
- Front Panel Lock Out
- Keypad / Auto Tare
- Auto Zero Tracking
- Adjustable Motion Detecting
- Adjustable Digital Filtering
- Time & Date
- (2) RS-232 Ports
- Print Configuration
- Scale ID Entry (30 Alpha Numeric)
- Weight Totalization (99 Weights)
- ID# Entry (20 Digits)
- Piece Counting

- 120 VAC Cord with Ground
- Selectable: NTEP 5,000 Divisions NON-NTEP 20,000 Divisions

Applications:

- Floor Scales
- Bench Scales
- Hopper Scales
- Tank Scales
- Fork Lift Scales
- Counting Scales
- General Purpose Weighing

Optional Features for SSCSW-20AT:

- 110 VAC Dry Contact Set Point
- RFL-Radio Frequency Link
- Bar Code Scanner (Pen or Laser)
- WiFi Transmitter Connection
- Ethernet Connection
- WI-CELL®-LT wireless communication from carriage to indicator now available

Specifications

Model	CSW-20AT	CSW-20AT-B	SSCSW-20AT	SSCSW-20AT-B
Power	120 VAC Adapter / 12 VDC ±10%	7.4 VDC 2600 mAH* Battery / 120 VAC	120 VAC Adapter / 12 VDC ±10%	7.4 VDC 2600 mAH* Battery / 120 VAC
Battery Operated	NO	YES	NO	YES
NON-NTEP Resolution	20,000 Division			
Legal for Trade	NTEP #06-070A1 Measurement Canada #AM-5778C NTEP Resolution 5000 Division			
Humidity	0-90% Non-condensing			
Dimensions	7" x 5.5" x 3" without Stand, +1 inch with Stand		7" x 6" x 3" without Stand, +1 inch with Stand	
Enclosure	Die Cast Aliminum		304 Stainless Steel Nema 4X	
Display	High Efficient, Bright (Adjustable) LED—6 Digits—0.56" High			
Input	0-15mv			
Temperature	10° to +40° Celsius			
Linearity	0.001% of Full Scale			
Accuracy	0.001% of Full Scale			
Load Cell Supply	5VDC at 150ma (8 each 350 ohm load cells)			
Battery Oprating Time	-	(1) 350 OHM Cell - 22hrs (4) 350 OHM Cell - 20hrs (8) 350 OHM Cell - 14hrs	-	(1) 350 OHM Cell - 22hrs (4) 350 OHM Cell - 20hrs (8) 350 OHM Cell - 14hrs
Ports	2 x RS-232			
Country of Origin	USA			

i81u812

[Contact US](#)

[718-336-5900](tel:718-336-5900)

[Returns](#)

[Store Policies](#)

[About Us](#)

• Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)

• Address: 4802 Glenwood Rd. Brooklyn, NY 11234

• © 2000 - 2019 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.

