



Ohaus FC5513+R01 Frontier 5000 Micro Series Benchtop Centrifuge, 120V, 24 x 1.5 / 2.0 ml, 200 rpm – 13,500 rpm

Frontier Micro centrifuges deliver high-speed operation for a range of essential lab applications, such as DNA/RNA preparation, ultrafiltration, and more. Biocontainment rotors enable research involving hazardous samples. Engineered with convenience of operation in mind, these centrifuges feature an intuitive interface, with all key parameters immediately accessible for observation and adjustment. The compact design saves valuable bench space in the lab.



Manufacture: Ohaus

SKU: 30370692

UPC:

840308902718

Weight: 30.00 lb

Free Ground Shipping
within the 48
continental US States

Please Call
(800)832-0055

Features

Dependable Benchtop Micro Centrifuges, Ideal for High-speed Lab Applications

- Excellent functionality when used with rotors compatible with 1.5/2.0ml or 5ml microtubes with high throughput & biocontainment options, spin columns, PCR strips, cryo tubes & hematocrit capillaries..
- Designed for ease of operation, Frontier Micro centrifuges feature convenient controls on an intuitive interface, allowing responsive operation – even when wearing gloves.
- Packaging all their functionality within a small footprint, Frontier Micro centrifuges save valuable space on the lab bench.

Specifications

Maximum Capacity (Rotor)	24 x 1.5 / 2.0 ml
Maximum Relative Centrifuge Force (x g)	17,317 g
Net Weight	13.1 kg (28.9 lb)

Speed Range	200 rpm – 13,500 rpm
Refrigeration Range (text)	Not applicable
Program memories	99
Rotor In Package	Not applicable
Acceleration Gear	10
Deceleration Gear	10
Lid lock	Mechanical
Safety Certification	CE; FCC
Power Consumption	170 W
Rotor Recognition Method	Manual
Pre-cool time	Not applicable
Power	AC Power (Included)
Rotor Compatibility	Angle 24 x 1.5 ml / 2.0 ml; Angle 24 x 1.5 ml / 2.0 ml Sealable; Hematocrit rotor, 24 × Capillaries; Angle 18 x 2 ml Spin Columns
Running Time	Quickspin; 10 sec to 99 h 59 min 59 sec; Continuous
Working Environment	36°F – 95°F, 80%RH, non-condensing 2°C – 35°C, 80%RH, non-condensing
Dimensions (Width)	277.0 mm (10.9 in)
Noise Level	
Dimensions (Height)	236.0 mm (9.3 in)
Display	LCD with backlight
Dimensions (Length)	356.0 mm (14.0 in)

i81u812

- Contact US

718-336-5900

Returns

Store Policies

About Us

- Phone: [\(800\)832-0055](tel:8008320055) or [\(718\)336-5900](tel:7183365900)
 - Chat with us via [WhatsApp Chat](#)
- Address: 4802 Glenwood Rd. Brooklyn, NY 11234
- © 2000 - 2024 scalesgalore.com (a division of Itin Scale Co., Inc.) All rights reserved.